25X1

					
INFORMATION REPORT			DF PAGE FOR SPECIAL CONTROLS, IF ANY This material contains information affecting the National Defense of the United States within the meaning of the Espionage Laws, Title 18, U.S.C.		
REPARED	AND DISSEMINATED BY		Secs. 793 and 794, the		
	CENTRAL INTELLIGENCE A	GENCY	son is prohibited by		25X1
OUNTRY	ARMY review complet	ed.			
	ungary				
UBJECT			DATE DISTRIBUTED	14 mar 3	57
Te	echnical Data on Ponton Sect	ions and	NO. OF PAGES	NO. OF ENCLS.	
	Amphibian Truck				
			SUPPLEMENT TO REPO	PRT#	25X1
	THIS IS U	NEVALUATED INFO	RMATION		25X
	This report is the result of he Army, the Navy, and CIA a	a joint collected is dissemined	tion effort by the ted in accordance USAF review comp	with the	
NAVY revi	iew completed.	•	COM TOTION COMP	iotou.	
7.		·			25X1
f: en f: su cu	ections to bridge sites rom three sections of which ach and center ponton 1050 k sketch showin rom 2 mm thick steel plates. nd for 40-ton capacity three apacities closed (airtight) f the 16 and 40 ton bridge i -meter span is 280 kg each.	g /see ng the bridge/. For 16 ton ca ponton section pontons are emp	notice at end of x The positions are f pacity two position s are used. For h loyed. The model	eport for abricated sections igher designation	25X1 25X1 25X
s. f. e. f.	rom three sections of which ach and center ponton 1050 k sketch showin rom 2 mm thick steel plates and for 40-ton capacity three apacities closed (airtight) f the 16 and 40 ton bridge i	g /see ng the bridge/. For 16 ton ca ponton section pontons are emp	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet-	constructed 50 kg eport for abricated sections igher designation used for a	25X
5. 5. 5. 2. 2.	rom three sections of which ach and center ponton 1050 k sketch showin rom 2 mm thick steel plates and for 40-ton capacity three apacities closed (airtight) f the 16 and 40 ton bridge i	g see ng the bridge/. For 16 ton ca e ponton section pontons are emp as NPU. The wei	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet-	constructed 50 kg eport for abricated sections igher designation used for a	25X 1 25X
finer finer cu cu cu cu cu cu cu cu cu cu cu cu cu	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates and for 40-ton capacity three apacities closed (airtight) of the 16 and 40 ton bridge in the section of the section	ag see ag the bridge. For 16 ton ca ponton section pontons are empts. The weight	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet-	constructed 50 kg eport for abricated sections igher designation used for a made.	25X 1 25X
5: 6: 6: 2: 0: 14: 2:	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) f the 16 and 40 ton bridge formeter span is 280 kg each. If the truck are as follows: odel: ZISZ #151	ag see ag the bridge of the bridge of the bridge of the case ponton section pontons are empts. NPU. The weight amphibian truck	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet-	constructed 50 kg eport for abricated sections igher designation used for a made.	25X 1 25X
5: 6: 6: 2: 0: 14: 2:	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) f the 16 and 40 ton bridge is meter span is 280 kg each. If the truck are as follows:	ag see ag the bridge/. For 16 ton ca ponton section pontons are empl. NPU. The wei amphibian truck	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gun.	constructed 50 kg eport for abricated sections igher designation used for a made. ical data	25X 1 25X
2. M	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) f the 16 and 40 ton bridge if -meter span is 280 kg each. If the truck are as follows: dodel: ZISZ #151 P: 110 at 2,000 RPM	ag see ag the bridge/. For 16 ton ca ponton section pontons are empl. NPU. The wei amphibian truck	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gun. Located between	constructed 50 kg eport for abricated sections igher designation used for a made. ical data ed and	25X 1 25X
so fine en fin	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) of the 16 and 40 ton bridge in-meter span is 280 kg each. If the truck are as follows: indel: ZISZ #151 P: 110 at 2,000 RPM ength: 9m	ag see ag the bridge/. For 16 ton ca ponton section pontons are empl. NPU. The wei amphibian truck	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gun.	constructed 50 kg eport for abricated sections igher designation used for a made. ical data ed and	25X 1 25X
so fine en fin	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) f the 16 and 40 ton bridge if -meter span is 280 kg each. If the truck are as follows: dodel: ZISZ #151 P: 110 at 2,000 RPM	ag see ag the bridge/. For 16 ton ca pontons exection pontons ere emp amphibian truck Capacity: 2 Motor-Winch:	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gum. Located between body. Operation stern and bow.	constructed 50 kg eport for abricated sections igher designation used for a made. ical data ed and	25X 1 25X
S. F. C.	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) of the 16 and 40 ton bridge in-meter span is 280 kg each. If the truck are as follows: codel: ZISZ #151 P: 110 at 2,000 RPM ength: 9m idth: 2m	ag see ag the bridge/. For 16 ton ca pontons exection pontons ere emp amphibian truck Capacity: 2 Motor-Winch:	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gun. Located between body. Operation	constructed 50 kg eport for abricated sections igher designation used for a made. ical data ed and	25X 1 25X
s. s. f. eu	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) of the 16 and 40 ton bridge is meter span is 280 kg each. If the truck are as follows: odel: ZTSZ #151 P: 110 at 2,000 RPM ength: 9m idth: 2m peed: 50 km on road 15 km on water	g see ng the bridge/. For 16 ton ca ponton section pontons are emp s NPU. The wei amphibian truck Capacity: 2 Motor-Winch: Gears: 5 for	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gum. Located between body. Operation stern and bow. rward, I reverse. s-country type; ca ated or deflated f	constructed 50 kg eport for abricated sections igher designation used for a made. ical data ed and nose and al from	25X 1 25X
f. f	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) of the 16 and 40 ton bridge in-meter span is 280 kg each. If the truck are as follows: odel: ZISZ #151 P: 110 at 2,000 RPM ength: 9m idth: 2m peed: 50 km on road 15 km on water ropeller: 50 cm diameter	g see ng the bridge/. For 16 ton ca ponton section pontons are emp s NPU. The wei amphibian truck Capacity: 2 Motor-Winch: Gears: 5 fo Tires: Cross infl driv	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gun. Located between body. Operation stern and bow. rward, I reverse. s-country type; ca ated or deflated f er's seat.	constructed 50 kg eport for abricated sections igher designation used for a made. ical data ed and nose and al from	25X 1 25X
2. Sign 1. Sig	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) of the 16 and 40 ton bridge in-meter span is 280 kg each. If the truck are as follows: Odel: ZISZ #151 P: 110 at 2,000 RPM ength: 9m idth: 2m peed: 50 km on road 15 km on water ropeller: 50 cm diameter he truck was used for transp	g see ng the bridge/. For 16 ton ca ponton section pontons are emp amphibian truck Capacity: 2 Motor-Winch: Gears: 5 fo Tires: Cross infl driv corting personne	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gun. Located between body. Operation stern and bow. rward, I reverse. s-country type; ca ated or deflated f er's seat.	constructed 50 kg eport for abricated sections igher designation used for a made. ical data ed and nose and al from n be rom d and across	25X 25X 25X1
2. S. M. W. S. S. M. W. S. M. W. S. M. M. S. M.	rom three sections of which ach and center ponton 1050 k sketch showing rom 2 mm thick steel plates, and for 40-ton capacity three apacities closed (airtight) of the 16 and 40 ton bridge in-meter span is 280 kg each. If the truck are as follows: Odel: ZISZ #151 P: 110 at 2,000 RPM ength: 9m idth: 2m peed: 50 km on road 15 km on water ropeller: 50 cm diameter the truck was used for transpater.	g see ng the bridge/. For 16 ton ca ponton section pontons are emp amphibian truck Capacity: 2 Motor-Winch: Gears: 5 fo Tires: Cross infl driv corting personne	rn pontons weigh 9 notice at end of r The pontons are f pacity two ponton s are used. For h loyed. The model ght of the I beams was Soviet- The techn 5 men fully equipp mall gun. Located between body. Operation stern and bow. rward, I reverse. s-country type; ca ated or deflated f er's seat. l and cargo on lan	constructed 50 kg eport for abricated sections igher designation used for a made. ical data ed and nose and al from n be rom d and across	25X1

C-O-N-F-I-D-E-N-T-I-A-L

- 2 - 25X1


classified CONFIDENTIAL, is a drawing of the three-section ponton bridge, Model NPU. 25X1

Approved For Release 2008/08/05 : CIA-RDP80T00246A000601230001-8

- end -

C-O-N-F-I-D-E-N-T-I-A-L

Confidential



PONTON BRIDGE - MODEL NPU

CAPACITIES :

3 SECTIONS-

40 TONS

2 SECTIONS

16 TONS

25X1.



Confidential